



Ordering Information

Single Port PacketBand TDM Versions

PacketBand-TDM-1D

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE PB-TDM-1D

Software Options

Select number of Logical Links if >1 required for G.704 "Grooming":

Upgrade to 16 Lls	PB-TDM-1D-LL-16
Upgrade to 32 Lls	PB-TDM-1D-LL-32
Enhanced Security Pack for Management	PB-TDM-1D-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports	PB-TDM-1D-SFP
DC PSU option (replaces internal AC)	PB-TDM-1D-DC
Improved Stratum3 TCXO Oscillator	PB-ST3
Improved Stratum3 OCXO Oscillator (oven stabilised)	PB-ST30
Rack Kit for one unit	PB/RMK/3/S
Rack kit for 2 units side-by-side	PB/RMK/3/D

Approvals

Safety and emissions (EMC) approvals (CE and FCC)	included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required)	PB-TDM-1D-APP1

PacketBand-TDM-1E

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE with Asymmetrical and Plesiochronous clocking PB-TDM-1E

Software Options

Select number of Logical Links if >1 required for G.704 "Grooming":

Upgrade to 16 Lls	PB-TDM-1E-LL-16
Upgrade to 32 Lls	PB-TDM-1E-LL-32
LACP Option	PB-TDM-1E-LP
RSTP Option	PB-TDM-1E-RS
Enhanced Security Pack for Management	PB-TDM-1E-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports	PB-TDM-1E-SFP
DC PSU option (replaces internal AC)	PB-TDM-1E-DC
Improved Stratum3 TCXO Oscillator	PB-ST3
Improved Stratum3 OCXO Oscillator (oven stabilised)	PB-ST30
Rack Kit for one unit	PB/RMK/3/S
Rack kit for 2 units side-by-side	PB/RMK/3/D

Approvals

Safety and emissions (EMC) approvals (CE and FCC)	included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required)	PB-TDM-1E-APP1

PacketBand-TDM-1MC

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE PB-TDM-1MC

Software Options

Select number of Logical Links if >1 required for G.704 "Grooming":

Upgrade to 16 Lls	PB-TDM-1MC-LL-16
Upgrade to 32 Lls	PB-TDM-1MC-LL-32
LACP Option	PB-TDM-1MC-LP
RSTP Option	PB-TDM-1MC-RS
Enhanced Security Pack for Management.	PB-TDM-1MC-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports	PB-TDM-1MC-SFP
DC PSU option (replaces internal AC)	PB-TDM-1MC-DC
Improved Stratum3 TCXO Oscillator	PB-ST3
Improved Stratum3 OCXO Oscillator (oven stabilised)	PB-ST30
Rack Kit for one unit	PB/RMK/3/S
Rack kit for 2 units side-by-side	PB/RMK/3/D

Approvals

Safety and emissions (EMC) approvals (CE and FCC)	included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required)	PB-TDM-1MC-APP1

DB Manager

DBM LITE

Serial/LAN single device GUI. Free. Networks should consider options below. DBM/LITE

Single Work-Station DBManager Package

Single work-station DbManager with visibility/connectivity to 4 units.	DBM/1/4
Single work-station DbManager with visibility/connectivity to 10 units.	DBM1/10
Single work-station DbManager with visibility/connectivity to 25 units.	DBM/1/25
Single work-station DbManager with visibility/connectivity to 50 units.	DBM/1/50
Single work-station DbManager with visibility/connectivity unlimited number of units.	DBM/1/U
SNMP Traps & Alarms options for above DBM/SNMP/1	

4 Concurrent Work-Station DBManager Package

4 work-station DbManager with visibility/connectivity to 25 units.	DBM/4/25
4 work-station DbManager with visibility/connectivity to 50 units.	DBM/4/50
4 work-station DbManager with visibility/connectivity to unlimited number of units.	DBM/4/U
SNMP Traps & Alarms options for above DBM/SNMP/4	
Other larger versions of DbManger available.	

Cables

Cable Pack single E1/T1 PacketBand 2m	PB/cpack/1P
Crossed-cable pack for PB-TDM-1 if connecting to DCE	PB/Xcpack/1P
120 Ohm RJ45 to 75Ohm dual BNC conversion cable 20cm	PB/CPACK/75BNC/01
PacketBand serial controller cable only (included in all above)	PB/cont
Other cable lengths available. Please enquire.	

