



Ordering Information

Single Port PacketBand TDM Versions

PacketBand-TDM-1D

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE PB-TDM-1D

Software Options

Select number of Logical Links if >1 required for G.704 "Grooming":

Upgrade to 16 Lls PB-TDM-1D-LL-16
Upgrade to 32 Lls PB-TDM-1D-LL-32
Enhanced Security Pack for Management PB-TDM-1D-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports PB-TDM-1D-SFP
DC PSU option (replaces internal AC) PB-TDM-1D-DC
Improved Stratum3 TCXO Oscillator PB-ST3
Improved Stratum3 OCXO Oscillator (oven stabilised) PB-ST30

Rack Kit for one unit PB/RMK/3/S
Rack kit for 2 units side-by-side PB/RMK/3/D

Approvals

Safety and emissions (EMC) approvals (CE and FCC) included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required) PB-TDM-1D-APP1

PacketBand-TDM-1E

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE with Asymmetrical and Plesiochronous clocking PB-TDM-1E

Software Options

Select number of Logical Links if >1 required for G.704 "Grooming":

Upgrade to 16 Lls PB-TDM-1E-LL-16
Upgrade to 32 Lls PB-TDM-1E-LL-32
LACP Option PB-TDM-1E-LP
RSTP Option PB-TDM-1E-RS
Enhanced Security Pack for Management PB-TDM-1E-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports PB-TDM-1E-SFP
DC PSU option (replaces internal AC) PB-TDM-1E-DC
Improved Stratum3 TCXO Oscillator PB-ST3
Improved Stratum3 OCXO Oscillator (oven stabilised) PB-ST30

Approvals

Rack Kit for one unit PB/RMK/3/S
Rack kit for 2 units side-by-side PB/RMK/3/D
Safety and emissions (EMC) approvals (CE and FCC) included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required) PB-TDM-1E-APP1

PacketBand-TDM-1MC

Hardware Options

Single T1/E1 CESoPSN unit. (2xUTP) 10/100/GE (hardware populated for Multicast but order PB-TDM-1M-IGMP to enable feature when needed) PB-TDM-1MC

Software Options

Multicast Data RX using IGMP PB-TDM-1MC-IGMP
Select number of Logical Links if >1 required for G.704 "Grooming":
Upgrade to 16 Lls PB-TDM-1MC-LL-16
Upgrade to 32 Lls PB-TDM-1MC-LL-32
LACP Option PB-TDM-1MC-LP
RSTP Option PB-TDM-1MC-RS
Enhanced Security Pack for Management. PB-TDM-1MC-Sec1

Hardware Options

SFP Cage option for fibre WAN connection in addition to 2xUPT ports PB-TDM-1MC-SFP
DC PSU option (replaces internal AC) PB-TDM-1MC-DC
Improved Stratum3 TCXO Oscillator PB-ST3

Improved Stratum3 OCXO Oscillator (oven stabilised) PB-ST30
Rack Kit for one unit PB/RMK/3/S
Rack kit for 2 units side-by-side PB/RMK/3/D

Approvals

Safety and emissions (EMC) approvals (CE and FCC) included
ETSI/ANSI Approvals Protection for Leased Line connectivity (extra hardware required) PB-TDM-1MC-APP1

DB Manager

DBM LITE

Serial/LAN single device GUI. Free. Networks should consider options below. DBM/LITE

Single Work-Station DBManager Package

Single work-station DbManager with visibility/connectivity to 4 units. DBM/1/4
Single work-station DbManager with visibility/connectivity to 10 units. DBM1/10
Single work-station DbManager with visibility/connectivity to 25 units. DBM/1/25
Single work-station DbManager with visibility/connectivity to 50 units. DBM/1/50
Single work-station DbManager with visibility/connectivity unlimited number of units. DBM/1/U
SNMP Traps & Alarms options for above DBM/SNMP/1

4 Concurrent Work-Station DBManager Package

4 work-station DbManager with visibility/connectivity to 25 units. DBM/4/25
4 work-station DbManager with visibility/connectivity to 50 units. DBM/4/50
4 work-station DbManager with visibility/connectivity to unlimited number of units. DBM/4/U
SNMP Traps & Alarms options for above DBM/SNMP/4
Other larger version sof DbManger available.

Cables

Cable Pack for single E1/T1 PacketBand. 2m PB/cpack/1P
Crossed-cable pack for PB-TDM-1D if connecting to DCE PB/Xcpack/1P
PacketBand serial controller cable only (included in all above) PB/cont
Other cable lengths available. Please enquire.